



GLASSWOOL

Solution provider in glass fiber and binder – based
insulation material



GFI GLASSWOOL

Pipe Insulation





GFI GLASSWOOL

Pipe Insulation

Dimensions

NPS (inch)	1/2	3/4	1	1 1/2	2	2 1/2	3	4	5	6
ID (mm)	21	27	34	48	60	76	89	114	140	168
Length tolerance						± 5mm				
Thickness tolerance						± 5mm				

Technical Parameters

Product Name	Standard Thickness (mm)	Nominal Density (Kg/m ³)	Standard Size (mm)
GFI Glasswool	25 and 50	120 - 150	1000
Product Name	Max. Service Temperature		
GFI Glasswool	650 °C		

Temperature reduction specification

Nominal Pipe Size (Inch)	Thickness (mm)	Without Glasswool (°C)	With Glasswool (°C)
½ - 6	50	230 °C	45 - 48 °C

GFI GLASSWOOL

Pipe Insulation

Dimensions

NPS (inch)	1/2	3/4	1	1 1/2	2	2 1/2	3	4	5	6
ID (mm)	21	27	34	48	60	76	89	114	140	168
Length tolerance						± 5mm				
Thickness tolerance						± 5mm				

Technical Parameters

Product Name	Standard Thickness (mm)	Nominal Density (Kg/m ³)	Standard Size (mm)
GFI Glasswool	25 and 50	120 - 150	1000
Product Name	Max. Service Temperature		
GFI Glasswool	650 °C		

Temperature reduction specification

Nominal Pipe Size (Inch)	Thickness (mm)	Without Glasswool (°C)	With Glasswool (°C)
½ - 6	50	230 °C	45 - 48 °C

Handling and storage

GFI Glasswool using more environmental friendly binder.

Products are rigid and easy to install.

GFI Glasswool products are packed in cardboard cartoons as appropriate. The number of sections per pack depends on the size of the section.

